## APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Date	of filing in State Engineer's Office DEC 1 5 1978
Retu	rned to applicant for correction
Corr	ected application filed
Мар	filed
	The applicant Jack and/or Mary Hadwin
	Street and No. or P.O. Box No.  Nevada 89834  Nereby make application for permission to appropriate the public State and Zip Code No.
	rs of the State of Nevada, as hereinafter stated. (If applicant is a corporation, give date and place of incorpora-
tion;	if a copartnership or association, give names of members.)
1.	The source of the proposed appropriation is underground  Name of stream, lake or other source.
2.	The amount of water applied for is
_	The water to be used for. Quasi-Municipal (trailer park)
	Irrigation, power, mining, manufacturing, domestic, or other use.
4.	If use is for:
	(a) Irrigation (state number of acres to be irrigated)
	(b) Stockwater (state number and kinds of animals to be watered)
	(c) Other use (describe fully under "No. 12, Remarks")
	(d) Power:
	(1) Horsepower developed
	(2) Point of return of water to stream
<b>5</b> .	The water is to be diverted from its source at the following point: NE4SW4 section 15. T39N.
	R52E, MDB&M, or at a point from which the N <sup>1</sup> / <sub>4</sub> corner of said sec- Describe as being within a 40-acre subdivision of public survey, and by course and distance to a section corner. If on unsurveyed land, tion 15 bears N 2° 33' 00" E, a distance of 3925 feet.
6.	Place of use portions of the NE4SW4, SE4SW4, NW4SE4 and the SW4SE4  Describe by legal subdivision, if on unsurveyed land it should be so stated.  of section 15, T39N, R52E, MDB&M.
	Use will begin about Jan. 1 and end about Dec. 31 , of each year.  Day and Month Day and Month
8.	Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans and
	specifications of your diversion or storage works.) well, pump and pipeline to trailer  park.  State mainer in which water is to be diverted, whether by dam or other works, whether through pipes, ditches, flumes, or other conduits.

9.	Estimated cost of works \$10,	,000
0.	Estimated time required to construct works	3 years
1.	Estimated time required to complete the application to beneficial	use 3 years
2.	Remarks: For use other than irrigation or stock watering, state consumptive use.	•
pp	plicant Jack and /or Mary Hadwin	
Con		Charles C. Armuth, Jr. Agent 1262 Hannah Drive Elko, Nevada 89801
	APPROVAL OF STA	TE ENCINEED
ollo	This is to certify that I have examined the foregoing application owing limitations and conditions:	in, and do hereby grant the same, subject to the
pla rea	ght obtained under this permit will be dependentaced to beneficial use. It is also understood asonable lowering of the static water level. The (2) inch opening for measuring depth to water st be installed and maintained to prevent waste	that this right must allow for a his well shall be equipped with a . If the well is flowing, a valve
nus and nea nus Vor	d maintained in the discharge pipeline near the asurements must be kept of water placed to benest be installed before any use of water begins ork is filed.  No perforations shall be put in the productions.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion on casing from ground level to 100
nus and nea nus Mor	d maintained in the discharge pipeline near the asurements must be kept of water placed to benest be installed before any use of water begins ork is filed.  No perforations shall be put in the productions	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion on casing from ground level to 100
nus and nea nus Vor	d maintained in the discharge pipeline near the asurements must be kept of water placed to benees to be installed before any use of water begins ork is filed.  No perforations shall be put in the productions.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion on casing from ground level to 100
nus and nea nus Vor	d maintained in the discharge pipeline near the asurements must be kept of water placed to benefic to be installed before any use of water begins or is filed.  No perforations shall be put in the productions.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion on casing from ground level to 100
ind ind iea ius lor	d maintained in the discharge pipeline near the asurements must be kept of water placed to benefice the installed before any use of water begins on the filed.  No perforations shall be put in the production of	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion on casing from ground level to 100
ind inea inus lor ee	d maintained in the discharge pipeline near the asurements must be kept of water placed to benefic to be installed before any use of water begins on the production of perforations shall be put in the production of water to be appropriated shall be limited to the amount of water to be appropriated shall be ap	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 must be applied to beneficial use, and
nus ind nea nus lor ee	d maintained in the discharge pipeline near the asurements must be kept of water placed to beneficially be installed before any use of water begins on the production of perforations shall be put in the production of water to be appropriated shall be limited to the amount of water to be appropriated shall be limited to the amount of exceed.    1.0	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 unt which can be applied to beneficial use, and r second, but not to exceed 2.87
nus ind nea ius lor ee	d maintained in the discharge pipeline near the asurements must be kept of water placed to benefit be installed before any use of water begins ork is filed.  No perforations shall be put in the production of water to be appropriated shall be limited to the amount of water to be appropriated shall be limited to the amount of exceed.  1.0	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 unt which can be applied to beneficial use, and r second, but not to exceed 2.87
nd neadus or eee	d maintained in the discharge pipeline near the asurements must be kept of water placed to benefit be installed before any use of water begins on the production of water to be appropriated shall be limited to the amount of water to be appropriated shall be limited to the amount of exceed l.O cubic feet per llion gallons annually.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 unt which can be applied to beneficial use, and r second, but not to exceed 2.87
nd he ctu	d maintained in the discharge pipeline near the asurements must be kept of water placed to beneat be installed before any use of water begins on the production of of commencement of work shall be filed before.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 on casing from ground level to 100 on the can be applied to beneficial use, and resecond, but not to exceed 2.87  N/A  N/A
ind indicate the control of the cont	d maintained in the discharge pipeline near the asurements must be kept of water placed to benefit be installed before any use of water begins on the production of water to be appropriated shall be limited to the amount of water to be appropriated shall be limited to the amount of exceed l.O cubic feet per llion gallons annually.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 on casing from ground level to 100 on the can be applied to beneficial use, and resecond, but not to exceed 2.87  N/A  N/A
he ctu	d maintained in the discharge pipeline near the asurements must be kept of water placed to beneat be installed before any use of water begins on the production of of commencement of work shall be filed before.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 unt which can be applied to beneficial use, and r second, but not to exceed 2.87  N/A  N/A  N/A  N/A  N/A  N/A  N/A
The ot to the control of the control	d maintained in the discharge pipeline near the asurements must be kept of water placed to beneat be installed before any use of water begins on the installed.  No perforations shall be put in the production of of commencement of work shall be filed before.  In maintained in the discharge pipeline near the asure of of commencement of work shall be filed before.  The maintained in the discharge pipeline near the asure of of commencement of work shall be filed before.  The must be prosecuted with reasonable diligence and be completed.	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 on casing from ground level to 100 on the can be applied to beneficial use, and resecond, but not to exceed 2.87  N/A  N/A  N/A  N/A  N/A  N/A  July 15, 1984
he ot t	d maintained in the discharge pipeline near the surements must be kept of water placed to benefit be installed before any use of water begins on the filed.  No perforations shall be put in the production of water to be appropriated shall be limited to the amount of exceed.  I.Q	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 unt which can be applied to beneficial use, and r second, but not to exceed 2.87  N/A  N/A  N/A  N/A  N/A  N/A  June 15, 1984  July 15, 1984  June 15, 1987
musand meanus Wor fee  The not t mil Actu Proo Appl	d maintained in the discharge pipeline near the asurements must be kept of water placed to benefic to installed before any use of water begins on the installed.  No perforations shall be put in the production of water to be appropriated shall be limited to the amount of exceed line cubic feet performed to exceed line cubic feet performed to construction work shall begin on or before the must be prosecuted with reasonable diligence and be completed of of completion of work shall be filed before the must be prosecuted with reasonable diligence and be completed of of completion of work shall be filed before the must be prosecuted with reasonable diligence and be completed of of completion of work shall be filed before the must be prosecuted with reasonable diligence and be completed of of completion of work shall be filed before the made on or before the must be made on or before the made on the made o	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 on casing from grou
The lot the mill Acturate World Proof	d maintained in the discharge pipeline near the asurements must be kept of water placed to beneficial use shall be filed on or before	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion on casing from ground level to 100 on the second, but not to exceed 2.87  N/A  N/A  N/A  N/A  N/A  N/A  July 15, 1984  July 15, 1987  before  July 15, 1987  hereof, I PETER G: MORROS
musand meanus wor fee  The not t mill Actu Proo Appl Proo Appl Acom Comp	d maintained in the discharge pipeline near the asurements must be kept of water placed to beneficial use shall be filed on or before	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion of on casing from ground level to 100 on casing from grou
The lot t loom Proof	d maintained in the discharge pipeline near the asurements must be kept of water placed to beneficial use shall be filed on or before	point of diversion and accurate ficial use. The totalizing meter or before the Proof of Completion on casing from ground level to 100 on the second, but not to exceed 2.87  N/A  N/A  N/A  N/A  N/A  N/A  July 15, 1984  July 15, 1987  before  July 15, 1987  hereof, I PETER G: MORROS